

The ScanTube companies manufacture tubing for use where high temperature and high performance properties are required. The characteristics of fluoropolymers are chemical inertness, high heat resistance, low coefficient of friction, UV resistance and excellent electrical insulation properties.

ScanTube fluoropolymer tubing is ideal for chemical, electrical, automotive, mechanical and heat exchanger applications. The range of dimensions and tolerances shown here are standard metric sizes. ScanTube can manufacture many other sizes on a custom basis to meet your special requirements.

PTFE Metric sizes

ID [mm]	Tolerance +/-	Wall [mm]	Tolerance +/-	OD [mm]
2,00	0,10	0,50	0,10	3,00
2,00	0,10	1,00	0,20	4,00
3,00	0,15	0,50	0,10	4,00
3,00	0,15	1,00	0,20	5,00
4,00	0,15	0,50	0,10	5,00
4,00	0,15	1,00	0,20	6,00
5,00	0,20	0,50	0,10	6,00
5,00	0,20	1,00	0,20	7,00
6,00	0,20	0,50	0,10	7,00
6,00	0,20	1,00	0,20	8,00
7,00	0,20	0,50	0,10	8,00
7,00	0,20	1,00	0,20	9,00
8,00	0,20	0,50	0,10	9,00
8,00	0,20	1,00	0,20	10,00
10,00	0,30	1,00	0,20	12,00
12,00	0,30	1,00	0,20	14,00
14,00	0,40	1,00	0,20	16,00
16,00	0,40	1,00	0,20	18,00
18,00	0,50	1,00	0,20	20,00
20,00	0,50	1,00	0,20	22,00

Note: Packed in coils of random production lengths. Cut lengths and custom packing on request.
This price list is strictly confidential and may not be distributed to other parties.

ScanTube makes no guarantee of results and assumes no obligation of any liability whatsoever in connection with this information.